

Simplicity 2

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
 Date of issue: 08 July 2019 Revision date: 08 July 2019 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Trade name : Simplicity 2

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Dental product, dental adhesive for use by Dental professionals.

1.3. Supplier

Inter-Med, Inc. / Vista Dental Products
 2200 South Street
 Racine, WI 53404
 T: (877)-418-4782

1.4. Emergency telephone number

Emergency number : 800-424-9300 (North America)
 +1 (703) 527-3887 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

| | |
|---|--|
| Flammable liquids Category 2 | Highly flammable liquid and vapor |
| Skin corrosion/irritation Category 2 | Causes skin irritation |
| Serious eye damage/eye irritation Category 2 | Causes serious eye irritation |
| Skin sensitization, Category 1 | May cause an allergic skin reaction |
| Reproductive toxicity Category 1B | May damage fertility or the unborn child |
| Specific target organ toxicity (single exposure) Category 3 | May cause drowsiness or dizziness |

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) : Highly flammable liquid and vapor
 Causes skin irritation
 May cause an allergic skin reaction
 Causes serious eye irritation
 May cause drowsiness or dizziness
 May damage fertility or the unborn child

Precautionary statements (GHS US) : Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Keep container tightly closed.
 Use explosion-proof electrical/ventilating/lighting equipment
 Use only non-sparking tools.
 Avoid breathing vapors, spray.
 Wash hands thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Contaminated work clothing must not be allowed out of the workplace
 Wear eye protection, protective gloves.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
 If inhaled: Remove person to fresh air and keep comfortable for breathing
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If exposed or concerned: Get medical advice/attention.
 If skin irritation or rash occurs: Get medical advice/attention.

Simplicity 2

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

If eye irritation persists: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
In case of fire: Use media other than water to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | GHS-US classification |
|---|----------------------|-----------|---|
| Acetone | (CAS.No.) 67-64-1 | 45 – 70 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 |
| Bis[2-[(2-methyl-1-oxoallyl)oxy]ethyl] dihydrogen benzene-1,2,4,5-tetracarboxylate | (CAS.No.) 51156-91-3 | 10 – 30 | Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Comb. Dust |
| 2-hydroxyethyl methacrylate | (CAS.No.) 868-77-9 | 10 – 30 | Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 |
| 2-Propenoic acid, 2-methyl-, (1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] ester | (CAS.No.) 1565-94-2 | 1 – 5 | Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317 |
| Benzoic acid, 4-(dimethylamino)-, ethyl ester | (CAS.No.) 10287-53-3 | 0.5 – 1.5 | Repr. 1B, H360 |

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Give artificial respiration if necessary. If you feel unwell, seek medical advice.
- First-aid measures after skin contact : Immediately rinse with plenty of water (for at least 15 minutes). Take off immediately all contaminated clothing and wash it before reuse. Get immediate medical advice/attention.
- First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects : May damage fertility or the unborn child.
- Symptoms/effects after inhalation : May cause drowsiness or dizziness.
- Symptoms/effects after skin contact : Causes skin irritation. May cause an allergic skin reaction.
- Symptoms/effects after eye contact : Causes eye irritation.
- Symptoms/effects after ingestion : May cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
- Unsuitable extinguishing media : None known.

5.2. Specific hazards arising from the chemical

- Fire hazard : Highly flammable liquid and vapor. On combustion, forms: carbon oxides (CO and CO₂).

Simplicity 2

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- Explosion hazard : May form flammable vapor-air mixture. Vapors may travel long distances along ground before igniting/flashing back to vapor source.
- Reactivity in case of fire : Stable under normal conditions.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Exercise caution when fighting any chemical fire.
- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Keep away from open flames, hot surfaces and sources of ignition.

6.1.1. For non-emergency personnel

- Protective equipment : Use personal protective equipment as required. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. In case of inadequate ventilation wear respiratory protection.
- Emergency procedures : Stop leak if safe to do so. Ventilate spillage area. Take precautionary measures against static discharge. Eliminate all ignition sources if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of residues refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
- Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Wear personal protective equipment. Do not breathe vapors. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical/ventilating/lighting equipment.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Use explosion-proof electrical/ventilating/lighting equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Storage conditions : Keep only in original container. Store in a well-ventilated place. Keep cool.
- Incompatible materials : Strong acids. Strong bases.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| | | |
|--|-----------------|---------|
| Bis[2-[(2-methyl-1-oxoallyl)oxy]ethyl] dihydrogen benzene-1,2,4,5-tetracarboxylate (51156-91-3) | | |
| Not applicable | | |
| Acetone (67-64-1) | | |
| ACGIH | Local name | Acetone |
| ACGIH | ACGIH TWA (ppm) | 250 ppm |

Simplicity 2

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Acetone (67-64-1) | | |
|--|-----------------------------------|--|
| ACGIH | ACGIH STEL (ppm) | 500 ppm |
| ACGIH | Remark (ACGIH) | TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI |
| ACGIH | Biological Exposure Indices (BEI) | 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift - Notations: Ns |
| ACGIH | Regulatory reference | ACGIH 2019 |
| OSHA | OSHA PEL (TWA) (mg/m³) | 2400 mg/m³ |
| OSHA | OSHA PEL (TWA) (ppm) | 1000 ppm |
| OSHA | Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |
| NIOSH | NIOSH REL (TWA) (mg/m³) | 590 mg/m³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 250 ppm |
| 2-hydroxyethyl methacrylate (868-77-9) | | |
| Not applicable | | |
| 2-Propenoic acid, 2-methyl-, (1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] ester (1565-94-2) | | |
| Not applicable | | |
| Benzoic acid, 4-(dimethylamino)-, ethyl ester (10287-53-3) | | |
| Not applicable | | |

8.2. Appropriate engineering controls

- Appropriate engineering controls : Provide local exhaust or general room ventilation to minimize vapor concentrations. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
- Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Impermeable protective gloves

Eye protection:

Safety glasses with side shields

Skin and body protection:

Long sleeved protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. An approved organic vapor respirator/supplied air or self-contained breathing apparatus must be used when vapor concentration exceeds applicable exposure limits

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|---------------------|
| Physical state | : Liquid |
| Appearance | : Liquid. |
| Color | : Pale yellow |
| Odor | : acetone odor |
| Odor threshold | : No data available |
| pH | : No data available |
| Melting point | : < 0 °C |
| Freezing point | : No data available |
| Boiling point | : > 50 °C |
| Flash point | : No data available |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Flammability (solid, gas) | : Not applicable. |

Simplicity 2

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|---------------------------------|---------------------|
| Vapor pressure | : No data available |
| Relative vapor density at 20 °C | : No data available |
| Relative density | : No data available |
| Solubility | : No data available |
| Log Pow | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosion limits | : No data available |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

No hazardous decomposition products known at room temperature.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|-----------------------------|---|
| Acute toxicity (oral) | : Not classified (Based on available data, the classification criteria are not met) |
| Acute toxicity (dermal) | : Not classified (Based on available data, the classification criteria are not met) |
| Acute toxicity (inhalation) | : Not classified (Based on available data, the classification criteria are not met) |

| Acetone (67-64-1) | |
|----------------------------|--|
| LD50 oral rat | 5800 mg/kg |
| LD50 dermal rabbit | > 15700 mg/kg |
| LC50 inhalation rat (mg/l) | 50100 mg/m ³ (Exposure time: 8 h) |

| | |
|--|---|
| Skin corrosion/irritation | : Causes skin irritation. |
| Serious eye damage/irritation | : Causes serious eye irritation. |
| Respiratory or skin sensitization | : May cause an allergic skin reaction. |
| Germ cell mutagenicity | : Not classified (Based on available data, the classification criteria are not met) |
| Carcinogenicity | : Not classified (Based on available data, the classification criteria are not met) |
| Reproductive toxicity | : May damage fertility or the unborn child. |
| Specific target organ toxicity – single exposure | : May cause drowsiness or dizziness. |

| Bis[2-[(2-methyl-1-oxoallyl)oxy]ethyl] dihydrogen benzene-1,2,4,5-tetracarboxylate (51156-91-3) | |
|--|-----------------------------------|
| Specific target organ toxicity – single exposure | May cause respiratory irritation. |

| Acetone (67-64-1) | |
|--|------------------------------------|
| Specific target organ toxicity – single exposure | May cause drowsiness or dizziness. |

Simplicity 2

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|--|---|
| Specific target organ toxicity – repeated exposure | : Not classified (Based on available data, the classification criteria are not met) |
| Aspiration hazard | : Not classified (Based on available data, the classification criteria are not met) |
| Viscosity, kinematic | : No data available |
| Symptoms/effects | : May damage fertility or the unborn child. |
| Symptoms/effects after inhalation | : May cause drowsiness or dizziness. |
| Symptoms/effects after skin contact | : Causes skin irritation. May cause an allergic skin reaction. |
| Symptoms/effects after eye contact | : Causes eye irritation. |
| Symptoms/effects after ingestion | : May cause gastrointestinal irritation, nausea, vomiting and diarrhoea. |
| Other information | : Likely routes of exposure: ingestion, inhalation, skin and eye. |

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : This material has not been tested for environmental effects.

| Acetone (67-64-1) | |
|-------------------|--|
| LC50 fish 1 | 4.74 - 6.33 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss) |
| EC50 Daphnia 1 | 10294 - 17704 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static]) |
| LC50 fish 2 | 6210 - 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| EC50 Daphnia 2 | 12600 - 12700 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| ErC50 (algae) | > 2800 mg/l 14days |

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

| Acetone (67-64-1) | |
|-------------------|-------|
| BCF fish 1 | 0.69 |
| Log Pow | -0.24 |

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1993 Flammable liquids, n.o.s. (Acetone), 3, II
UN-No.(DOT) : UN1993
Proper Shipping Name (DOT) : Flammable liquids, n.o.s.
Acetone
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT) : II - Medium Danger

Simplicity 2

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
Emergency Response Guide (ERG) Number : 128
Other information : No supplementary information available.

Transportation of Dangerous Goods

Transport document description : UN1993 FLAMMABLE LIQUID, N.O.S. (Acetone), 3, II
UN-No. (TDG) : UN1993
Proper Shipping Name (Transportation of Dangerous Goods) : FLAMMABLE LIQUID, N.O.S.
TDG Primary Hazard Classes : 3 - Class 3 - Flammable Liquids
Packing group : II - Medium Danger
TDG Special Provisions : 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the hazard or hazards posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A) of Part 3 (Documentation). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4 (Dangerous Goods Safety Marks). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a)UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S.; (b)UN1851, MEDICINE, LIQUID, TOXIC, N.O.S.; (c)UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S.; (d)UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S.; or (e)UN3249, MEDICINE, SOLID, TOXIC, N.O.S. An example in Canada is the "Food and Drugs Act". (3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment: (a)UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b)UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS. SOR/2014-306, 150 - An emergency response assistance plan (ERAP) is required for these dangerous goods under subsection 7.1(6) of Part 7 (Emergency Response Assistance Plan).
Explosive Limit and Limited Quantity Index : 1 L
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 5 L

Simplicity 2

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea

Transport document description (IMDG) : UN 1993 FLAMMABLE LIQUID, N.O.S. (Acetone), 3, II
UN-No. (IMDG) : 1993
Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, N.O.S.
Class (IMDG) : 3 - Flammable liquids
Packing group (IMDG) : II - substances presenting medium danger
Limited quantities (IMDG) : 1 L

Air transport

Transport document description (IATA) : UN 1993 Flammable liquid, n.o.s. (Acetone), 3, II
UN-No. (IATA) : 1993
Proper Shipping Name (IATA) : Flammable liquid, n.o.s.
Class (IATA) : 3 - Flammable Liquids
Packing group (IATA) : II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Acetone (67-64-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

CERCLA RQ 5000 lb

2-hydroxyethyl methacrylate (868-77-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

2-Propenoic acid, 2-methyl-, (1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] ester (1565-94-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Benzoic acid, 4-(dimethylamino)-, ethyl ester (10287-53-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

2-hydroxyethyl methacrylate (868-77-9)

Listed on the Canadian DSL (Domestic Substances List)

2-Propenoic acid, 2-methyl-, (1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] ester (1565-94-2)

Listed on the Canadian DSL (Domestic Substances List)

Benzoic acid, 4-(dimethylamino)-, ethyl ester (10287-53-3)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Bis[2-[(2-methyl-1-oxoallyl)oxy]ethyl] dihydrogen benzene-1,2,4,5-tetracarboxylate (51156-91-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Acetone (67-64-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

2-Propenoic acid, 2-methyl-, (1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] ester (1565-94-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Benzoic acid, 4-(dimethylamino)-, ethyl ester (10287-53-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Bis[2-[(2-methyl-1-oxoallyl)oxy]ethyl] dihydrogen benzene-1,2,4,5-tetracarboxylate (51156-91-3)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

Simplicity 2

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetone (67-64-1)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

2-Propenoic acid, 2-methyl-, (1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] ester (1565-94-2)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

Benzoic acid, 4-(dimethylamino)-, ethyl ester (10287-53-3)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations

No additional information available

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 08 July 2019

Full text of H-phrases:

| | |
|------|--|
| H225 | Highly flammable liquid and vapor |
| H315 | Causes skin irritation |
| H317 | May cause an allergic skin reaction |
| H319 | Causes serious eye irritation |
| H335 | May cause respiratory irritation |
| H336 | May cause drowsiness or dizziness |
| H360 | May damage fertility or the unborn child |

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.