

MATERIAL SAFETY DATA SHEET

ZYGLO® PENETRANT ZL-56

1. <u>IDENTIFICATION</u>

Company: MAGNAFLUX

Address: 3624 West Lake Avenue, Glenview, Illinois 60026

Telephone No.: 847-657-5300 (Off-Hour Emergency Number - CHEMTREC - 1-800-424-9300).

Product Use: Fluorescent inspection penetrant

Packages: 1 gallon cans, 5 gallon pails, 20 and 55 gallon drums.

NFPA Rating: Health 1, Flammability 1, Reactivity 0

PIN (Canada): None

Revision Date: March 29, 2010

2. HAZARDOUS INGREDIENTS

<u>Ingredient</u>	<u>Wt./Wt. %</u>	<u>CAS #</u>	<u>TLV</u>	<u>PEL</u>	<u>LD</u> 50	<u>LC</u> 50
Alcohols (C_{12} - C_{18}), ethoxylated					2.6 g/kg	
propoxylated	15-40	69227-21-0	not avail.	not avail.	(oral/rat)	not avail.
Alcohols (C_{11} - C_{16}), secondary,					2.4 g/kg	
ethoxylated	10-30	68131-40-8	not avail.	not avail.	(oral/rat)	not avail.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Bland oily liquid which may irritate the skin and eyes. Difficult to ignite, but will burn vigorously if engulfed in fire.

POTENTIAL HEALTH EFFECTS

Skin Contact: Can irritate by removing natural skin oils on long or repeated exposures.

Eyes: Irritating

Inhalation: Not significant. When heated or sprayed, ZL-56 vapors may cause dizziness and nausea.

Ingestion: Not significant in small (mouthful) amounts.

Medical conditions known to be aggravated by exposure to product: None

4. FIRST AID

Skin Contact: Wash off with soap and water. Use soothing lotion.

Eyes: Rinse carefully under upper and lower eyelids using plenty of water.

Inhalation: Remove to fresh air if dizzy or nauseated.

Ingestion: Do not induce vomiting. Accidental ingestion of a small mouthful is not expected to cause significant harm.

NOTE: In all severe cases, contact physician immediately. Local telephone operators can furnish number of regional poison control center.

5. **FIRE HAZARD**

Conditions of flammability: Heating above 200°F (93°C) in presence of ignition sources. Flash point (Bulk): Minimum 200°F (93°C) (Pensky-Martens closed cup).

Flammable limits in air: 1% to 6%

Extinguishing media: Carbon dioxide, foam.

Special fire fighting procedures: Keep containers cool with water spray.

Hazardous combustion products: Smoke, soot, oxides of carbon and nitrogen.

Unusual fire hazards: None

6. ACCIDENTAL RELEASE MEASURES

Mop up or sweep up with absorbent. (For disposal, see Section 13.)

7. HANDLING AND STORAGE

Avoid breathing spray mist.

Avoid repeated or prolonged skin contact.

Avoid eye contact.

Store away from heat sources.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Controls: None, unless applied as spray. Use where ventilation will carry spray mist away from occupied areas.

Personal protection: Wear safety glasses to protect eyes. Wear nitrile rubber gloves if hand exposure is unavoidable.

Respirator with filter if sprayed in enclosed, unventilated space.

9. PHYSICAL PROPERTIES

Initial boiling point (bulk): Min. 455°F (235°C) (ASTM D-86) Vapor pressure: <0.10 mm @ 70°F(21°C)

VOC Content (EPA Method 24):350 g/LVapor density:Heavier than airDensity/sp. gravity:1.01Evaporation rate:NegligibleWater solubility:0 (emulsifies into water)Appearance:Green, oily liquid

pH: Neutral Odor: Mild odor

10. STABILITY AND REACTIVITY

Stability: Stable Incompatibility: None

Hazardous decomposition products: Soot, oxides of carbon and nitrogen if heated to combustion temperature.

Reactivity: None

11. TOXICOLOGICAL INFORMATION

Carcinogenicity: Contains no known or suspected carcinogens listed with OSHA, IARC, NTP, or ACGIH.

Threshold limit value: 5 mg/m□ for oily mist.

WHMIS information (Canada): According to available information, the ingredients have not been found to show reproductive toxicity,

teratogenicity, mutagenicity, skin sensitization, or synergistic toxic effects with other materials.

2. ECOLOGICAL INFORMATION

No data is available on ZL-56. It emulsifies into water and is biodegradable. Its low bulk vapor pressure may exempt it from VOC restrictions.

DISPOSAL

All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator.

14. TRANSPORTATION

U.S. DOT: 49 CFR 172.101 Hazardous Materials Table

Non-Aerosol

Proper shipping name: None, not restricted

Hazard class or division:

Identification No.:

Packing Group:

None

15. **REGULATORY INFORMATION**

TSCA: All ingredients are listed in TSCA inventory.

CERCLA: Not reportable

SARA TITLE III, Section 313: No reportable ingredients

California Proposition 65: Warning: This material may contain trace amounts of chemicals known to the state of California to cause cancer

and/or birth defects and/or reproductive harm.

WHMIS Class (Canada): D-2B

Note: This MSDS has been prepared to meet WHMIS (Canada) requirements with the exception of using 16 headings.

16. OTHER INFORMATION

Revision Statement: Section 13 Supersedes: April 13, 2007

Prepared by: Laurie Marx, Production Chemist